

Dunbrik A1 Concrete Flue Liners

for domestic chimneys

Flue Costing 200 mm id

Tel: 01924 373694

Email: tech@dunbrik.co.uk Web: www.dunbrik.co.uk

200ID-7m-offset-2-23B

Typical Flue Detail Costing Costing for: House type House with 200mm I.D. Flue Customer ref. Chimney Height 7017

Date Ву

Costing ref

02 February 2024

SJ October 2023 Price list

Plot number	Price list		October 2023	
Components	Product	Qty	Prices	Cost
	code	_	each	£
Throat lintel/gather unit 800mm wide	200TL800	1	94.75	94.75
200mm flue liner bend 22.5 degrees	200B	4	18.29	73.16
200mm flue liner 600mm tall	200L600	8	18.74	149.92
200mm flue liner 230mm tall	200L230	2	11.21	22.42
200mm flue liner 150mm tall	200L150	2	8.85	17.70
Flue liner sealant 310ml	Dunseal	6	6.68	40.08
Infill aggregate 22kg mix for void	Dunfil	20	6.98	139.60
Cannon pot 450mm tall red	Cann450R	1	50.90	50.90
Topguard birdguard cowl 260 tall red	TG260R	1	101.36	101.36
Flue notice plate	Plate	1	7.73	7.73
310ml Skeleton Gun	Sealgun	1	6.40	6.40
Red polypropylene air brick 220mm x 72mm	REDG930	3	0.92	2.76
High impact styrene black cavity sleeve 218mm x 72mm	CSG935	3	5.03	15.09
Smoke pellet tube	Smoke	1	11.34	11.34

Cost ex-works * 733.21 Delivery charge 60.00 793.21 Goods VAT @ 20% 158.64 Total 951.85

All prices are ex-works, valid for 30 days and are subject to VAT.

Charge for individually plotting multiple flue orders is £30 per plot.

Free delivery for orders over £1,000 nett invoice value (ex-Vat) to UK mainland excluding the Highlands of Scotland (POA).

All trading is subject to our standard conditions of sale (copy available).

Notes

This flue costing is based on information provided. Please have your architect check the costing to your drawings prior to ordering. to ensure that it meets with your requirements. Please also check the pot/terminal style and colour.

For construction guidance refer to the flue illustration and the installation guide available on our website www.dunbrikflues.co.uk

The infill is based on a 303mm x 375mm void between the liners and masonry

Please ensure that the flue and chimney are constructed in accordance with Building regulations part J

Dunbrik (Yorks) Ltd 172 Ferry Lane, Stanley, Wakefield WF3 4LT - Registered in England 419512



Typical flue detail Sample 200mm I.D. flue liner system for open fire with offset.

Date: October 2023

Ref: 200id-7m-offset-2-23B

Telephone: 01924 373694 Email: tech@dunbrik.co.uk Web: www.dunbrik.co.uk

CANN450 1 No. 200L150 1 No. 200L150 2 No. 200B Bends In Order To Backset Flue System. Dunfil used to fill void between flue liner and Plan at Top of Stack surrounding masonry. Voids between flue liners and masonry to be filled with Dunfil 8 No. 200L600-Plan at First Floor Level -2 No. 200B Bends In Order 1 No. 200L230 To Offset Flue System Left. 1 No. 200L230 200TL800 Plan at Ground Floor Level Chimney Height 7037mm from FFL to U/S of chimney pot. Dunbrik A1 Concrete Flue Liner System to BS EN 1857

Notes

Chimney Height of 7037mm from FFL to underside of chimney pot.

Please have your architect check this typical flue illustration to your drawings to ensure it meets both your requirements and current building regulations.

ALL DIMENSIONS ARE SHOWN IN MILLIMETRES NOT TO SCALE



Dunbrik (Yorks) Ltd

Tel: 01924 373694 Email: tech@dunbrik.co.uk domestic flue & chimney systems

The checklist is based on Building Regulations ADJ Appendix A. with Dunbrik flue liner system data. The builder/installer should insert details of the actual fireplace opening sizes, actual ventilation installed and any variations to the usual data.

Typical Flue Detail Costing 200ID-7m-offset-2-23B For Costing ref Site at Plot number

Dunbrik 200mm id A1 concrete flue liners House with 200mm I.D. Flue System House type Date 31 Jan 2024 200 mm id Customer ref. Chimney Height 7017

Checklist for hearths, fireplaces, flues and chimneys

		intractor, a cop	by should be offered to the main contractor.	and		
1	Items listed in ADJ Appendix A Building address, where work has been ca	rried out	Details for builder to complete or amend			
				Amend		
2	Identification of hearth, fireplace, chimney	or flue.	Fireplace in lounge			
3	Firing capability: solid fuel/gas/oil/all		All			
1	Intended type of appliance. State type or n		For gas fire or solid fuel fire			
	If open fire give finished fireplace opening	dimensions.	500mm by 550mm maximum or equivalent area			
Ventilation provisions for the appliance		Through wall ventilation				
	State type and area of permanently open a	ır vents	15,700 sq mm minimum			
	Chimney or flue construction State the type or make and whether new o	r existing.	New masonry chimney with: Dunbrik A1 concrete flue liners to BSEN1857			
)	Internal flue size (and equivalent flue height calculated natural draught gas appliances		200mm internal diameter			
:)	If liners are used confirm they are correctly in accordance with manufacturers instructi state jointing materials used.	jointed ons and	Tongue downwards into rebate and joined with Dunseal fireproof mortar			
I)	If an existing chimney has been refurbishe new liner, type or make of liner fitted.	d with a				
()	Details of flue outlet terminal	Outlet detail	Cannon pot 450mm tall			
	(Complies with:	BSEN13502:2002			
)	Number and angle of bends.		4 bends ref 200B at 22.5 degrees			
)	Provision for cleaning and recommended t	requency.	Annually via fireplace opening			
7	Hearth. Form of construction. New or existing		New			
	Increation and testing after completion		As diagram 25 in ADJ Tests carried out by:			
Inspection and testing after completion Test (Appendix E in AD J 2002) and results		า ยอเจ ผสกายน อนเ มง.				
	Flue inspection results	√isual				
		Sweeping Coring ball				
		Smoke				
_		Spillage				
	I/We the undersigned confirm that the a relevant requirements in Part J of Sch		are correct. In my opinion, these works comply wit Building Regulations.	h the		
	Print name & title		Profession			
	Capacity		Tel no			
	Address		Postcode			
	Signed		Date			
	Registered membership of (e.g. Gas Safe	tv. OFTEC. HE	ETAS. NACE. NACS)			