

Stellgas Terminal Insert

The Stellgas is a clay gas terminal to insert into a chimney pot serving a "precast" gas flue to keep obstructions from entering the flue. It has outlet slots around the sides and a 180mm spigot to fit a Dunbrik Cannon or Roll Top chimney pot.

(Note: British Standard BS1289 requires a suitable cowl to be fitted to a gas flue to guard against blockage from birds, bird nests and other debris.)

Gas Fire Suitability

The Stellgas is used for gas flues which have a gas fire suitable for precast flues fitted. These are "class 2" gas fires up to 7kW input tested by the fire manufacturer as suitable.

Unsuitable Fires and Appliances

The Stellgas is **not** suitable for chimneys or flues which have:-

- solid fuel fires
- oil burning appliances
- open grate gas fires
- a gas fire with an input above 7kW

A **Topguard** steel cowl is a suitable birdguard and rain cowl for these applications.

Installation

Apply a bed of mortar to the top rim of the chimney pot and insert the Stellgas terminal. Gently tamp down. Check that the joint is properly made and remove excess mortar.

Stell380 Stellgas Terminal Insert		
Product reference	Stell380	
Diameter	240mm	
Spigot external	180mm	
Spigot internal	150mm	
Height	380mm	
Weight	10.8 kg	
Pallet quantity	50	
Standard colour	Red	
Optional colour	Buff	

Householders Information

This information should be passed to the householder to ensure that the **Stellgas insert is removed** should a gas fire with an input above 7kW be installed or if the chimney has a solid fuel fire or an oil burning appliance fitted.